

www.thalesgroup.com/germany

Beam Focusing in Satcom TWTs Including Thermal Electrons

5th ITG Vacuum Electronics Workshop 2016, Session 2.3-3
P.Birtel, J. Wegener, J.-F. David


Security and mobility in a networked world.

THALES

- **Motivation**
- **Basics of electron beam focusing in a TWT**
- **Modeling of thermal electrons in gun and delay line**
- **Case study: Satcom TWT**
 - Beam focusing including thermal electrons
 - Effects on other TWT parameters (Gain, RF power etc.)
- **Conclusions**

This work is supported by Deutsches Zentrum für Luft- und Raumfahrt (DLR) and by Centre National d'Études Spatiales (CNES).






Satcom Traveling Wave Tube

Beam focusing critical!
(and expensive)

Thermal problems
Efficiency degradation



Simulated electron trajectories in the delay line with RF drive

- Beam focused by its *rotation***

- $\dot{v}_r = -\eta(\mathbf{E}_r + \mathbf{v}_\phi \times \mathbf{B}_z)$; B_z axial magnetic field


- Beam rotation created by change in magnetic flux (Busch's theorem)**

- $\frac{v_\phi}{r} = \frac{\eta}{2} \left(B_z - B_c \left(\frac{r_c}{r} \right)^2 \right)$;


B_c magnetic field on cathode, r_c cathode radius, r beam radius


- Equilibrium between focusing and de-focusing:**

- $B_z^2 = \frac{2}{r} \sqrt{\frac{I}{2\pi\epsilon\eta v}} + B_c^2 \frac{r_c^4}{r^4} = B_B^2 + B_c^2 \frac{r_c^4}{r^4}$; B_B Brillouin field



- **Periodic Permanent Magnets (PPM)** instead of solenoid
- **Only little magnetic field outside the TWT**
- **Field strength limited, maximum allowable period**







- **Gun2 (Thales)**

- 2.5D Gun optics, no RF

- **MVTRAD (Thales)**

- 2.5D beam-wave interaction




- **Non-zero initial kinetic energy of electrons (cathode normal and transversal)**

- $\overline{E_n} = \overline{E_t} = kT$




- $\overline{E_n + E_t} = 2kT$ (ca. 0.2eV)

- **Current density distribution according to Lambert's Law**

- $J(\theta) = J_0 \frac{\cos \theta}{\pi}$






- **Multiple emitted particles per emission point (e.g. 5)**
- **Equal emission energy ($2kT$) and equal charge per particle**
- **Varying angles with respect to cathode normal, constrained by Lambert's Law**




- **Satellite communication TWT design study**
- **CW tube (no gridded gun)**
- **Beam area compression ~50**
- **Beam efficiency ~32% (high linearity)**
- **Target beam fill factor 40%**
- **PPM peak field ~0.3T**


- **Very different conditions at first magnet for different electron „classes“ ($\pm v_r, v_\phi$)**
- **No common perfect solution**




- **Non-thermal beam well focused**
- **Beam diameter significantly increased by thermal electrons**




- **Goal: similar focusing for all „classes“**
- **If possible, keep cathode field and PPM strength unchanged**
- **Trial-and-error process**
- **Quality of non-thermal and thermal focusing only loosely correlated**




no thermals
first design




no thermals
second design





with thermals
first design




with thermals
second design



- Negligible effect on beam efficiency
- Small effect on gain (~1.5dB)




- Little effect on the electron velocity spectrum at output
- Spectrum slightly widens (ca. 200V)




- **Accurate prediction of beam focusing requires chaining of Gun and interaction simulation tools**
- **Predictive value of the simulation significantly improved by adding thermal electrons**
- **Thermal focusing very sensitive to the first PPM magnets**

Thank you for your attention!




- **Zero-drive**
 - Choice of beam radius, overall focusing field, cathode field
 - Gun optics code (Gun2) for beam injection design
- **Beam extension under drive**
 - Beam-wave interaction code (MVTRAD)
 - Ideal beam, or chaining with gun code
- **Inclusion of thermal electrons**
 - Initial transverse velocities in gun code
 - Chaining with interaction code

- **No focusing field**
- **5 particles per point (5 „classes“)**
- **Radial and azimuthal velocity components at beam waist**
- **Disparate starting conditions for PPM focusing**
- **Effects depend on beam area compression**




Velocities at beam waist, no focusing field



- **First design (significant body current)**
- **5 thermals seem sufficient**

| Discretization | Body current / % |
|-----------------|------------------|
| No thermals | 0 |
| 3 thermals | 1.14 |
| 5 thermals | 1.49 |
| 8 thermals | 1.55 |
| 5 thermals, 4kT | 3.22 |

5 thermals
4kT initial velocities



- **Focusing critically dependent on beam injection design**
- **Focusing sensitive to accurate modeling of magnetic field in beam injection area**
- **Field on cathode helpful to focus electrons with initial v_r , strong beam rotation in gun helpful with initial v_ϕ**
- **Non-thermal beam quality and thermal beam quality only loosely correlated...**
- **... but zero drive and RF drive beam quality strongly correlated**

- **Gun2 (Thales): Electron gun optics, zero-drive focusing**
 - 2.5D Gun optics, self-consistent static particle trajectory solver
 - Space-charge limited emission model (Child-Langmuir)
 - Finite-difference space charge field calculation, fixed-point iteration
- **MVTRAD (Thales): Focusing with RF drive**
 - 2.5D self-consistent beam-wave interaction
 - Electric field: Superposition of delay line field and space charge field
 - Frequency domain, finite-element, particle-in-cell solver
- **Auxiliary tools (e.g. magnetostatic field computation)**