

Passive Mode-Locking of Two Helical-Type Gyro-TWTs at sub-THz Frequencies

Alexander Marek¹, Lukas Feuerstein¹, Stefan Illy¹, Manfred Thumm^{1,2}, Chuanren Wu¹
and John Jelonnek^{1,2}

¹IHM, ²IHE, Karlsruhe Institute of Technology (KIT), Kaiserstraße 12, 76131 Karlsruhe, Germany

ABSTRACT

New sources for the generation of ultra-short coherent radio frequency (RF) pulses at a reasonable output power of more than a few Watts in the sub-THz frequency range are gaining fundamental interest in the research community. Those RF sources might become the key components of future THz diagnostic and spectroscopy systems [1].

In this presentation, a new sub-THz source for the generation of trains of coherent high-power ultra-short pulses at 263 GHz is presented. The investigated frequency is an established figure for continuous wave DNP-NMR (400 MHz) application and, therefore, the investigated source could lead to the development of novel time-domain DNP-NMR methods [1].

The new pulsed source uses the mechanism of passive mode-locking of two helically gyro-TWTs [2] as it was first proposed in [3] and experimentally shown in [4] for the Ka-band. The principle of passive mode-locking is well known from laser physics. At microwave frequencies, it can be realized in a feedback loop of two vacuum electron tubes, one operated as amplifier, the other one as nonlinear saturable absorber [3]. The nonlinear absorber strongly attenuates low-power signals while it is almost transparent at high-power levels. In this way, it narrows the pulses. A fraction of the oscillating pulses is decoupled from the feedback loop, which results in a train of coherent high-power ultra-short pulses.

The pulsed source presented here is an extended version of the originally proposed setup in [3,4] with the aim to increase the possible fields of application. The usage of a high-gain helical gyro-TWT [5] instead of an ordinary helical gyro-TWT as amplifier enables the operation of the passive mode-locked oscillator in the hard excitation regime, while the original proposal is limited to an operation in the soft excitation regime. Further benefits are provided by a novel feedback system [6], which enables alternative operation regimes for the two coupled helical gyro-TWTs. Besides the original purpose as a mode-locked oscillator, the developed feedback system allows the realization of a two-stage amplifier and the possibility of operating the devices as backward wave oscillators.

In combination, these extensions make such a system of coupled helical gyro-TWTs a promising new microwave source for future time-domain spectroscopy applications.

References

- [1] K. O. Tan et al., Sci. Adv., vol. 5, Art. no. 1, 2019, doi: 10.1126/sciadv.aav6909.
- [2] G. G. Denisov et al., IEEE Trans. Plasma Sci., vol. 26, Art. no. 3, Jun. 1998, doi: 10.1109/27.700785.
- [3] N. Ginzburg et al., Tech. Phys. Lett., vol. 41, Art. no. 9, Sep. 2015, doi: 10.1134/S1063785015090047.
- [4] N. S. Ginzburg et al., Phys. Rev. Applied, vol. 16, no. 5, p. 54045, Nov. 2021, doi: 10.1103/PhysRevApplied.16.054045.
- [5] S. V. Samsonov et al., IEEE Electron Device Lett., vol. 41, Art. no. 5, 2020, doi: 10.1109/LED.2020.2980572
- [6] A. Marek et al., IEEE Trans. Electron Devices, vol. 67, Art. no. 12, 2020, doi: 10.1109/TED.2020.3028531.