

AN INNOVATIVE MINICHANNEL COOLING SYSTEM FOR GYROTRON CAVITIES

Alberto Leggieri¹, Ferran Albajar², Stefano Alberti³, Kostantinos A. Avramidis⁴, Rosa Difonzo⁵, Lukas Feuerstein⁶, Eleonora Gajetti⁵, Gerd Gantenbein⁶, J  r  my Genoud³, Jean-Philippe Hogge³, Stefan Illy⁶, John Jelonnek⁶, George Latsas⁴, Fran  ois Legrand¹, Christophe Lievin¹, Rodolphe Marchesin¹, Tomasz Rzesnicki⁶, Ioannis Tigelis⁴, Francisco Sanchez², Laura Savoldi⁵, Sebastian Stanculovic⁶, Athanasios Zelkas⁴ and Manfred Thumm⁶

¹Microwave & Imaging Sub-Systems, THALES V  lizy-Villacoublay, France, F-78141

²Fusion for Energy, Barcelona, Spain, E-08019

³Swiss Plasma Center, EPFL, Lausanne, Switzerland CH-1015

⁴Department of Physics, National and Kapodistrian University of Athens, Athens, Greece, GR-157 84

⁵Dipartimento Energia "Galileo Ferraris", Politecnico di Torino, Torino, Italy, I-10129

⁶IHM, Karlsruhe Institute of Technology, Karlsruhe, Germany, D-76131

ABSTRACT

Several improvements have been made on gyrotron solutions in order to maximize power and efficiency levels. The Thales TH1507U 1.5 MW for W7-X [1-2] and the TH1509U 170 GHz ITER gyrotron [3-4] represent the state of the art of these technologies. Increasing performances are constantly demanded, especially for future DEMO gyrotrons [5] where the heat load on the cavity wall is one of the major limiting factors [6-7]. In this frame, an improved mini-channel cavity cooling circuit has been developed and a mock-up has been manufactured. Compared to existing solutions [6-8], the proposed system increases the heat exchange while limiting thermo-mechanical stress and anisotropic deformations. The structure consists of two coaxial elements, where the fluid flow is placed as close as possible to the heated wall to increase heat exchange, and an adaptive profile of the outer element dilates and displaces during the operation to limit stress. The proposed solution can be realized by traditional mechanical processes and proven brazing techniques. Compared to Raschig rings cooling solution, for the same peak heat load of 1.85 kW/cm² and water flow of 65 l/min, a preliminary single-step simulation by PoliTO, based on the TH1507U cavity, shows a max temperature reduced from 222  C to 165  C with a stress level around 250 MPa, giving margin of 50 MPa before plasticization. Full loop multiphysics simulations are being performed with NKUA and a mock-up has been manufactured in order to be tested at KIT for technological validation.

Acknowledgments: This work is supported by EUROfusion and Euratom Research and Training Programme 2014–2018 and 2019–2020 Grant No. 633053 as well as Programme 2021-2025 grant No 101052200. The views expressed herein do not necessarily reflect those of the European Commission.

References

- [1] A. Leggieri et al, "THALES TH1507 140 GHz 1 MW CW Gyrotron for W7-X Stellarator", IRMMW-THz 2019.
- [2] K. Avramidis et al, "Towards a 1.5 MW, 140 GHz gyrotron for the upgraded ECRH system at W7-X", Fusion Engineering and Design, Elsevier 2020.
- [3] A. Leggieri et al, "Progress on TH1509U 170 GHz 1 MW European Gyrotron Program", IEEE IVEC 2022.
- [4] T. Rzesnicki et al, "Experimental Testing of the European TH1509U 170-GHz 1-MW CW Industrial Gyrotron – Long Pulse Operation", IEEE EDS, Vol.43, Issue 4, 2022, pp. 623-626.
- [5] J. Jelonnek et al, "European research activities towards a future DEMO gyrotron". 10th International Workshop "Strong Microwaves and Terahertz Waves: Sources and Applications", 2017.
- [6] S. Illy, et al, "Investigation of a Mini-Channel Cavity Cooling Concept for a 170 GHz, 2 MW Coaxial-Cavity Gyrotron" 44th IRMMW-THz, 2019.
- [7] A. Bertinetti et al, "Design, Test and Analysis of a Gyrotron Cavity Mock-up cooled using Mini-Channels", IEEE Transactions on Plasma Science, IEEE. 2018, Vol.46, Issue 6, 2018, pp. 2207 – 2215.
- [8] L. Savoldi et al, "Multiphysics simulator for the resonator of MW-class CW gyrotrons for fusion applications: a validation roadmap", Energies, Vol. 14, Issue 23, 2021, p. 8027.