

DEVELOPMENT AND QUALIFICATION OF THE THALES TH1509U EUROPEAN 170 GHZ 1 MW CW INDUSTRIAL GYROTRON

Alberto Leggieri¹, Ferran Albajar², Stefano Alberti³, Konstantinos A. Avramidis⁴, Ruggero Bertazzoni², Falk H. Braunmueller³, Antonio Cammi⁵, Ioannis Chelis⁴, Davide Dall'Acqua², Rosa Difonzo⁶, Lukas Feuerstein⁷, Eleonora Gajetti⁶, Gerd Gantenbein⁷, Jérémy Genoud³, Jérémy Gontard¹, Timothy P. Goodman³, Jean-Philippe Hogge³, Stefan Illy⁷, Carolina Introini⁵, Zisis Ioannidis⁴, John Jelonnek⁷, Jianbo Jin⁷, Sophie Kohler¹, François Legrand¹, Christophe Lievin¹, Rodolphe Marchesin¹, Ijaze M. Oumar¹, Tomasz Rzesnicki⁷, Francisco Sanchez², Laura Savoldi⁶, Sebastian Stanculovic⁷, Ioannis Tigelis⁴, Etienne Vallée¹ and Manfred Thumm⁷

¹THALES, Vélizy-Villacoublay, France 78140

²Fusion For Energy, Barcelona, Spain 08019

³Ecole Polytechnique Fédérale de Lausanne, Swiss Plasma Center, Lausanne, Switzerland 1015

⁴National and Kapodistrian University, Athens, Greece 15771

⁵Politechnic of Milan, Milan Italy 20133

⁶Politechnic of Turin, Turin Italy 10129

⁷Karlsruhe Institute of Technology, Germany 76131

ABSTRACT

High power gyrotrons produced by THALES Microwave & Imaging Sub-Systems (MIS) have shown particular reliability and graceful aging during decades [1]. Thales gyrotrons are developed in the frame of a strong collaboration with European research institutions where each partner provides its best expertise whose confrontation allows for an efficient risk assessment and decision making. In order to respond to the ECH&CD power needs of ITER and DTT [2], the TH1509U is based on a diode-type magnetron injection gun, a single-stage depressed collector and a TE_{32,9} cavity mode with an axial magnetic field of 6.77 T to provide 1 MW CW output at 170 GHz. A Gaussian TEM₀₀ beam is generated by a quasi-optical system including a launcher antenna, phase correcting mirrors and a CVD diamond window. The design has been optimized by integrating last generation subassemblies, including the cathode structure, the high-voltage feedthroughs and the body insulation as well as the beam tunnel and the interaction cavity, with particular care to maximize the power output while suppressing the excitation of parasitic modes [3]. The cooling circuits have been upgraded to further enhance the power load handling capability and a dedicated filament control system has been introduced to improve stability. The TH1509U gyrotron has undergone a scan of the body voltage from 20 to 26 kV with beam current ranging from 40 to 46 A showing the complete absence of parasitic modes and efficiency variation from 22% to 40% [4]. The unit has demonstrated a power of 1.03 MW at the output window with efficiency in excess of 40% during 5 consecutive 100 s stable pulses. The tests are progressing to optimize the gyrotron performance.

References

- [1] A. Leggieri et al, "THALES TH1507 140 GHz 1 MW CW Gyrotron for W7-X Stellarator", 44th IRMMW THz 2019, Paris.
- [2] A. Leggieri et al. "Industrial Qualification of the THALES TH1509U European 170 GHz 1 MW CW Gyrotron", 25th IVEC, Monterey, 2024.
- [3] T. Rzesnicki et al. "Parasitic-Modes Free, High-Performance Operation of the European 1 MW, 170 GHz Short-Pulse Prototype Gyrotron for ITER", IRMMW-THz, Montreal, 2023.
- [4] F. Braunmueller et al. "Results on the 1 MW CW 170 GHz gyrotron TH1509UA for ITER and DTT at the FALCON test stand", 22nd EC workshop, Daejeong, 2024.