

DESIGN AND ELECTROMAGNETIC ANALYSIS OF AN INPUT CAVITY FOR 648 MHz INDUCTIVE OUTPUT TUBES

Hirwa Sakindi Alain^{1,2}, Jiaqiu Tian^{1,2}, Dingyu Gu¹, Shaomeng Wang^{1,2}, Zhigang Lu^{1,2}, Yubin Gong^{1,2}

¹National Key Laboratory of Science and Technology on Vacuum Electronics, ²Terahertz Radiation and Application Key Laboratory of Sichuan Province, University of Electronic Science and Technology of China, China

E-mail of corresponding author: ybgong@uestc.edu.cn

Primary topic: Vacuum Electronic and Discharge Devices and their Applications; Secondary topic: Microwave Tubes; Presentation: Poster

ABSTRACT

Inductive Output Tubes (IOTs) are widely used high-power RF amplifiers for accelerator and broadcast systems, where the input cavity must provide efficient electron bunching and stable RF coupling. This work presents the design and electromagnetic analysis of a 648 MHz input cavity with the anode attached to the shell, as shown in Fig. 1. The cavity incorporates key components including a loop coupler for input excitation, a 5 mm Al₂O₃ insulator, cathode, Window, focus electrode, and Grid, optimized using CST Studio Suite simulations.

The cavity was simulated under a cathode potential of -70 kV and a grid bias of 350 V, with a sinusoidal excitation at 648 MHz. Electromagnetic simulations reveal excellent impedance matching with a reflection coefficient S_{11} of -30.11 dB precisely at 648 MHz, indicating low return loss and effective power transfer into the cavity. Voltage monitors positioned at the cavity centre and 5 mm offset record peak values of 54.83 V and 59.02 V, respectively, suggesting a usable RF field distribution for beam modulation. Particle trajectory tracking in Fig. 3 shows current collision on the anode and grid. These results demonstrate the cavity's suitability for IOT applications, achieving high Q-factor potential and coupling efficiency suitable for multi-kW operation. Future work will integrate this input section with the output cavity for full device validation [1-2]. This work was Supported by National natural science foundation of China (Grant No.62527804).




Fig.1. Proposed input cavity




Fig.2. Reflection Coefficient at 648MHz




Fig.3. Current Collision on Anode & grid

References

- [1] A. J. GILMOUR JR., Klystrons, Traveling Wave Tubes, Magnetrons, Crossed-Field Amplifiers, and Gyrotrons (Artech House, Norwood, MA, 2011).
- [2] R. L. IVES et al., IEEE Trans. Electron Devices 52 (2005) 673.