

DESIGN AND SIMULATION OF A 434 MHz INDUCTIVE OUTPUT TUBE

Dingyu Gu^{1,2}, Jiaqiu Tian^{1,2}, Hirwa Sakindi Alain^{1,2}, Shaomeng Wang^{1,2}, Zhanliang Wang^{1,2}, Qingying Yi^{1,2}, Yubin Gong^{1,2}

¹ National Key Laboratory of Science and Technology on Vacuum Electronics, ² Terahertz Radiation and Application Key Laboratory of Sichuan Province, University of Electronic Science and Technology of China, China

E-mail of corresponding author: ybgong@uestc.edu.cn

Presentation: Oral

Primary Topic: Vacuum Electronic and Discharge Devices and their Applications

Secondary Topic: Grid Controlled Tubes

ABSTRACT

The inductive output tube (IOT) is a linear-beam amplifier in which an RF grid-controlled electron gun directly bunches the beam, thereby enabling high-efficiency and high-linearity amplification [1]. This paper presents the design and simulation of the input cavity, electron gun, and output cavity of a 434 MHz IOT.

In this tube, electrons are emitted from a spherical cathode heated by an internal heater. A spoke-grid structure is employed, and the grid is placed in close proximity to the cathode, with a cathode-grid spacing of 0.7 mm. The RF signal is applied directly between the cathode and the grid, so that beam density modulation is established in the electron-gun region [2]. The grid is connected to the grounded cavity housing, and insulating ceramic spacers electrically isolate the housing from both the cathode and the grid.




Fig. 1 Cross-section of the input cavity




Fig. 2 RF output power

The device is simulated in CST Studio Suite 2024. Under operating conditions, with an input RF power of 1500 W, the peak cathode-to-grid RF voltage reaches 770 V, and the maximum beam current is 16 A. The cathode is biased at -60 kV, while the grid bias relative to the cathode is -300 V. In the absence of RF drive, the dc beam current is approximately 0.23 A. The density-modulated electron beam then passes through the grounded anode aperture and enters the output section. The output cavity adopts a re-entrant resonant-cavity structure, and the overall efficiency reaches 47%, with a peak output power of up to 227 kW.

This work is supported by National natural science foundation of china (Grant No.62527804).

References

- [1] E. L. WRIGHT, K. T. NGUYEN, J. A. PASOUR, S. J. COOKE, B. LEVUSH, J. J. PETILLO, and M. CUSICK, in Proceedings of 2009 IEEE International Vacuum Electronics Conference, April 2009, pp. 117–118.
- [2] M. KAUSHIK and L. M. JOSHI, J. Electromagn. Waves Appl. 29 (2015) 2027–2037.