

CMOS-Sensor Calibration for the Measurement of Field Emission Electron Currents

Matthias Hausladen¹, Ali Asgharzade¹, Mathias Bartl¹, Andreas Schels², Philipp Buchner¹, Rupert Schreiner¹

¹OTH Regensburg, D-93053 Regensburg, Germany

²Ketek GmbH, München, Germany

ABSTRACT

The use of field emission electron sources (FES) in X-ray sources or ionization vacuum gauges is still uncommon due to the restricted lifetime of field emission arrays (FEAs), often caused by high current loads. In [1], we showed that the lifetime-limiting effects (degradation) can be significantly reduced by distributing a total emission current across multiple FES-Chips. Similarly, the lifetime of a single FEA-chip depends on the emission distribution across its individual emitters.

However, it was found that the emission current of a FEA is usually distributed very inhomogeneously [2]. To investigate current distribution and its temporal behavior, we developed a CMOS-based imaging method capable of resolving current distributions on FEAs quantitatively over several orders of magnitude by mapping shares of spot signal intensities onto the measured integral current [3].

The mathematical description of the image sensor signal presented in [3], derived from a modified version of Kramers' law [4], has now been extended by a calibration constant C_C , enabling the determination of individual field emitter currents from the raw optical spot signal S_{Raw0} :

$$S_{Raw0} = C_C \cdot t_E \cdot I \cdot U^b \rightarrow I = \frac{S_{Raw0}}{C_C \cdot t_E \cdot U^b}$$

Here, t_E denotes the exposure time of the image sensor, I the cathode current, and U the cathode's extraction voltage or the electron's acceleration voltage respectively. The voltage exponent b is a simplified linear approximation, describing the electron-photon conversion of bremsstrahlung [4], as well as additional absorptive effects [3]. If C_C is known, an emission current I_S can be calculated from S_{Raw0} and compared with the electric emission current I_e . For a n-doped FEA-chip (5-10 Ω cm, Fig. 1a) this comparison is presented in Fig. 1b. The results show that the image-signal-derived current I_S matches the actual emission current I_e with an average accuracy of approximately 2 % over 5 min and a standard deviation of 3 %





Fig. 1: a) SEM image of the Si-FEA. b) Comparison of the calculated signal current I_S vs the emission current I_e .

References

- [1] M. Hausladen *et al.*, *J. Vac. Sci. Technol. B*, (2024), doi: [10.1116/6.0003233](https://doi.org/10.1116/6.0003233).
- [2] C. Langer *et al.*, *J. Vac. Sci. Technol. B*, (2020), doi: [10.1116/1.5134872](https://doi.org/10.1116/1.5134872).
- [3] M. Hausladen *et al.*, *MDPI Sensors*, (2025), doi: [10.3390/s25051529](https://doi.org/10.3390/s25051529).
- [4] K. Müller-Sievers, *Biophysik*, (1973), doi: [10.1007/BF01191242](https://doi.org/10.1007/BF01191242).