

EXPERIMENTAL ANALYSIS OF ADVANCED COOLING SOLUTIONS FOR CAVITIES OF MULTI-MW CW GYROTRONS

S. Stančulović¹, R. Difonzo², G. Gantenbein¹, S. Illy¹, J. Jelonnek¹, T. Ruess¹, T. Rzesnicki¹, L. Savoldi²

¹*Institute for Pulsed Power and Microwave Technology, Karlsruhe Institute of Technology (KIT), Kaiserstr. 12, 76131 Karlsruhe, Germany*

²*MAHTEP Group, Dipartimento Energia "Galileo Ferraris", Politecnico di Torino (PoliTo), Torino, Italy*

Institute for Pulsed Power and Microwave Technology (IHM), Karlsruhe Institute of Technology, Karlsruhe, Germany



Outline



Politecnico
di Torino



- High power CW gyrotron cavity cooling – mini-channels (MC) cooling approach
- KIT experimental set-up based on induction heating for examination of cavity cooling techniques
- Tests on MC mock-ups
- Current work - upgrade of the KIT cavity cooling test stand
- Conclusion and outlook



EUROfusion

Institute for Pulsed Power and
Microwave Technology (IHM)



Cavity cooling



Politecnico
di Torino




■ What is this all about?

- Developing of an advanced cooling for resonators of future 2 MW CW gyrotrons.

■ Why we need this?

- If not sufficiently cooled (e.g. Raschig Rings cooling), the very high thermal load on cavity wall (ca. 2 kW/cm²), after ca. 0.2 s leads to a cavity deformation that kills the nominal mode.

K. A. Avramidis et al., "Numerical studies on the influence of cavity thermal expansion on the performance of a high-power gyrotron", IEEE Trans. Electron Devices, January 2018, DOI: 10.1109/TED.2017.2782365.



EUROfusion

Institute for Pulsed Power and
Microwave Technology (IHM)



Cavity cooling



Politecnico
di Torino



■ Numerical analysis of cavity cooling

- Currently used cooling techniques in european gyrotrons, such as Raschig rings cooling and annular gap cooling, are not sufficient for applications in 2 MW CW fusion gyrotrons.
- New aproach with ***mini-channels cooling*** was systematically investigated and developed using numerical calculations.
- Work at KIT: K. A. Avramidis, S. Ruess, P. C. Kalaria, P. T. Brücker.
- Work at Politecnico Torin (PoliTo): L. Savoldi, A. Bertinetti, A. Allio, R. Difonzo.
- Output – publications of ca. 10 papers, several EUROfusion reports and a bachleor thesis.



Cavity cooling



Politecnico
di Torino



■ Previous work

■ Before 2020:

- Numerical simulations, design and construction of a mini-channel mock-up, installing the experimental set-up (K. A. Avramidis, S. Ruess, J. Weggen).
- Definition of requirements, ordering and commissioning of the induction heater MINAC, first experiments (P. C. Kalaria, S. Stančulović).

■ Since 2020:


- Experiments with different mock-ups, validation of the multi-physics simulations (KIT - S. Stančulović, PoliTo – L. Savoldi, R. Difonzo).



Block diagram of experimental set-up



Politecnico
di Torino




Mini-channel cooling mock-up, thermocouples (TC1... TC16), PT100 thermometers, pressure sensors, flow meter, MINAC 6/10 inductor heater with hand-held transformer and the inductor head, as well as SIMATIC S7-300® hardware and a computer with WIN CC® software.



Set-up with induction heater



Politecnico
di Torino




Components and mock-ups




Politecnico
di Torino



Cu with 100 μm Ni-layer



Cu 3D-printed





KIT
Karlsruhe Institute of Technology




KIT MC mock-up




Politecnico
di Torino



- Cavity geometry
 - 170 GHz, 2 MW, coaxial longer pulse gyrotron
 - $\varnothing_i = 59$ mm
 - 40 MCs, semicircular cross section, $r_{MC} = 1,4$ mm



Thales MC mock-up



Politecnico
di Torino



- Cavity geometry
 - TH1507U (W7-X)
 - $\varnothing_i = 46$ mm
- TCs issue



Cooling tests



Politecnico
di Torino



- Different power levels: from 1800 W up to 3600 W with MINAC 6/10 and up to 17000 W with MINAC 25/40 (max heating power level defined with device internal interlock).
- Different flow rates: from 3 l/min up to 20 l/min.
 - Low flow rates (up to 5 l/min) – higher temperature rise and higher accuracy of calorimetric measurements
 - High flow rates – more accurate pressure drop measurements, turbulent flow
- Different mock-ups:
 - MC KIT mock-ups: with Glidcop, Cu (3D-printed) and Cu with 100 μm Ni-layer cavities.
 - Thales mock-ups with MC and Raschig Rings (RR) cooling (Glidcop material).



Cooling tests




Politecnico
di Torino




■ Evaluation of the thermal-hydraulic (TH) numerical simulations

- EM simulation (CST software) of the heat load as input for TH calculations – spatial distribution and power level calibration



Cooling tests


- Evaluation of the thermal-hydraulic (TH) numerical simulations
 - Validation of the predictions of the TH simulation (PoliTo)



S. Stanculovic, et al., "Calibration of the KIT test setup for the cooling tests of a gyrotron cavity full-size mock-up equipped with mini-channels", Fusion Engineering and Design, vol. 172, June 2021, available online, doi: 10.1016/j.fusengdes.2021.112744.



Temperature increase across mock-up



Cooling tests



Politecnico
di Torino




■ Investigation of the cooling performances

■ Calorimetric measurements

- ❑ Max. heat load on the inner cavity wall ca. 220 W/cm^2 (10% of expected value in 2 MW CW gyrotron) → **MAIN CHALLENGE!**
- ❑ In comparison with Cu mock-up the mock-up with $100 \text{ }\mu\text{m}$ Nickel layer has an increase of ca. 20% of the induced heat load.

Calorimetric power for Cu Mock-up with Ni-layer



Cooling tests




Politecnico
di Torino



■ Investigation of the cooling performances

- Measurements of the temperature increase at different flow rates and heating power levels (transient and steady-state case)



Measured temperatures of KIT mock-up after 6 min heating with 3300 W and the total flowrate of 10 l/min



EUROfusion

Institute for Pulsed Power and
Microwave Technology (IHM)



Upgrade of the test stand



Politecnico
di Torino



- Increasing the measurement accuracy
 - New flow meter – 5 X higher accuracy up to 10 l/min (lower flow rate range).
 - New thermocouples – with reaction times < 0.1 s.
 - Increase of the sampling rate for factor 2.
- Improvements in EM simulations
 - Increase of mesh elements.
 - Increase of results spatial resolution.
 - Direct power calibration in EM simulations – calculated integral losses = measured calorimetric losses



EUROfusion

Institute for Pulsed Power and
Microwave Technology (IHM)



Increasing of the heat flux



Politecnico
di Torino



■ Rental device for comparisson tests

- Installation of the induction heater with 4 x higher nominal heating power – MINAC 25/40 (25 kW CW power)
- Perfoming the calorimetric measurements (estimation of the increase in the heat flux)
- Insertion of the thin ferromagnetic rings into the cavity (increase of the losses)
- Coating of the inner cavity wall with $> 300 \mu\text{m}$ Ni-layer



Increasing of the heat flux




■ Rental device for comparison tests

■ Preliminary results

Device	MINAC 6/10	MINAC 25/40
Nominal/achieved heating power	6/3.6 kW	25/17.2 kW
max. heat flux (under same conditions)	180 W/cm ²	730 W/cm ²
max. cavity ΔT @ 10 l/min	28.1°C	104.7°C
max. cavity ΔT @ 3 l/min	40.0°C	134.3°C

x 4

Upgrade with MINAC 50/80!!!



Compatibility



Politecnico
di Torino



- Other proposals for cavity cooling
 - Micro-Channels cooling (IPP, H. Laqua)
 - Triply Periodic Minimal Surfaces cooling (PoliTo, L. Savoldi)
 - Spray cooling (KIT)

- KIT test set-up is compatible with all these alternative cooling techniques



EUROfusion

Institute for Pulsed Power and
Microwave Technology (IHM)



Conclusion and outlook



- Experimental set-up at KIT for investigation of the cavity cooling techniques based on induction heating.
- Tests on mock-ups and results.
- Upgrade of the test set-up in order to increase the heat loads.
- Future steps: Tests with MINAC 50/80 and use of ferromagnetic inserts/layers in the cavity

Acknowledgements

Part of this work has been carried out within the framework of the EUROfusion consortium, funded by the European Union via the EURATOM research and training programme (grant agreement no. 101052200 - EUROFUSION). Part of the simulations were performed on the EUROfusion High Performance Computer (Marconi-Fusion). Views and opinions expressed are however those of the authors only and do not necessarily reflect those of the European Union or the European Commission. Neither the European Union nor the European Commission can be held responsible for them.

😊 Thank you for your attention 😊



Additional slides



Politecnico
di Torino



Karlsruhe Institute of Technology



EUROfusion






Politecnico
di Torino



Measrued temperatures @ 10 l/min and 17 kW



EUROfusion

