

THALES



EPFL



POLITECNICO
DI TORINO



UPGRADE OF THE EUROPEAN ITER 170 GHz 1 MW CW INDUSTRIAL GYROTRON (TH1509)

*Alberto Leggieri, David Bariou, Virgile Hermann, Francois Legrand, Gerald Lietaer,
Christophe Lievin, Rodolphe Marchesin, Philippe Thouvenin*

Thales AVS - Microwave and Imaging Subsystems (MIS)

Ferran Albajar, Francisco Sanchez
Fusion For Energy (F4E)

Stefano Alberti, Jean-Philippe Hogge
EPFL Swiss Plasma Center (SPC)

Andrea Allio, Rosa Difonzo, Laura Savoldi
**Politecnico di Torino
(PoliTO)**

Alessandro Bruschi, William Bin
**Institute for Plasma Science and
Technology (ISTP-CNR)**

Ioannis Chelis, George Latsas, Ioannis Tigelis,
National and Kapodistrian University of Athens

*Konstantinos A. Avramidis, Günter Dammertz, Gerd Gantenbein, Stefan Illy,
Zisis Ioannidis, John Jelonnek, Jianbo Jin, Ioannis Gr. Pagonakis,
Tomasz Rzesnicki, Manfred Thumm*
Karlsruhe Institute of Technology (KIT)

www.thalesgroup.com

OPEN

7th ITG International Vacuum
Electronics Workshop (IVEW) 2020



01

Introduction

02

Tube design and technical details

03

First prototype test results summary

04

First prototype expertize

05

Gyrotron evolution


06

Conclusions and
perspectives

OPEN

01

Introduction






OPEN

THALES

ITER Tokamak heating main features

- Ion Cyclotron Resonance Heating (ICRH), Tetrode or Diacode around 50 MHz
- Neutral Beam Injection. Two injectors to deliver two deuterium beams of 16.5 MW at 1 MeV particle energies
- **Electron Cyclotron Heating and Current Drive (ECH&CD) system: 24 gyrotrons at 170 GHz 1 MW CW**



OPEN

European Gyrotron Team

- The European contribution managed by the European Joint Undertaking for ITER, Fusion for Energy (F4E), under the control of EURATOM Agency.

- Fusion for Energy (F4E)



Tube specification
Magnet design



- Karlsruhe Institute of Technology (KIT),

- Swiss Plasma Center at EPFL Lausanne (SPC),

- National and Kapodistrian University of Athens,

- Politecnico di Torino (PoliTO)

- Istituto per la Scienza e Tecnologia dei Plasmi (ISTP-CNR)

- THALES Microwave and Imaging Subsystems



RF Design
Gun optimization



Beam Tunnel
Cavity cooling
Test set



POLITECNICO
DI TORINO



Εθνικό και Καποδιστριακό
ΠΑΝΕΠΙΣΤΗΜΙΟ ΑΘΗΝΩΝ
National and Kapodistrian
UNIVERSITY OF ATHENS



Technological design

THALES



THALES

02

Tube design and technical details



OPEN



THALES

Main design requirements

- Electron beam features compatible with ITER HV PSU
- Cavity mode selected to optimize electron beam coupling at 170 GHz with reduced Ohmic losses

Design baseline


- Depressed collector configuration: $V_b = +35$ kV, $V_c = -44.5$ kV
- Improved collector cooling and advanced beam sweeping
- Gaussian TEM beam lateral output
- Specific CVD diamond window
- Four coils SCM
- Diode-type MIG with reduced gun-cavity distance
- Specific corrugated BeO-SiC beam tunnel
- $TE_{32,9}$ cavity mode with $B_c = 6.78$ T
- Specific tapered launcher



Tube design and technical details


Magnetic configuration

- Main coils for the cavity field
- Reversed bucking coil for independent field control and reduced cathode to cavity spacing
- 2 Gun control coils
- low α mitigates parasitic modes and magnetic electron trapping



Electric configuration

- Robust technology compatible with fast switch on/off
- Flexible DC input (two working points: HVOP, LVOP)
- Diode MIG gun
 - Beam calculated with ESRAY and ARIADNE (KIT)
 - Electrode designed with E-field safety margin
 - Mature design for concentricity and electronic homogeneity




Main Design Parameters		
	HVOP	LVOP
Beam current I_b	40A	45A
Average pitch factor $\langle \alpha \rangle$	1.29	1.22
Cathode voltage	-44.5kV	-41.0 kV
Collector depression voltage V_b	35 kV	30 kV
Nominal accelerating voltage V_a	79.5 kV	71.0 kV

OPEN

Beam tunnel

- Energy spread calculated with 2D time-dependent code g2DRZ developed by SPC
- Minimized cathode-cavity distance for minimizing energy spread
- EU patent (KIT): cascade of dielectric (BeO-SiC) and indented metal (copper) rings




Large variations of
beam properties
(instabilities)



Spurious
oscillations
 E_{beam} spread



$\eta \downarrow$



Main Design Parameters	
Cavity mode	$TE_{32,9}$
Axial magnetic field B_c	6.78 T
Cavity mode purity	99.9 %
Long pulse operative frequency F_0	170 ± 0.3 GHz

Interaction cavity


- Interaction studied by the European code EURIDICE
- Same beam radius at cavity for both working points
- Non linear up-taper to the launcher
- Glidcop structure: conductivity/thermal expansion compromise
- EU patent (THALES): Raschig rings circuit pressure drops and mass flow compromise
- Enhance exchange surface and h by turbulent water flow in a porous media

OPEN

Tube design and technical details



Quasi-optical mode converter

- A slightly tapered helically cut hybrid launcher (helical perturbations dependent by $\lambda(z)$)
- The tapering reduces the quality factor to suppress spurious oscillations in the launcher itself



CVD-diamond window

- Edge-cooled single-disk CVD-diamond window for low-diffraction losses
- 97 % Gaussian TEM purity at the window







Stray radiation management

- Stray radiation partially extracted by a dedicated relief-sapphire window
- Remaining radiation dissipated onto the mirror box walls
- Mirror box cooled by a water filled double wall

Collector

- Designed to dissipate the full electron beam power up to 2 MW
- Power dissipation capability $\sim 1 \text{ kW/cm}^2$
- Max temperature $< 300^\circ\text{C}$
- EU Patent (KIT/IPP): optimized beam spread by axial and transversal magnetic sweeping




Vertical sweep only

Vertical sweep +
constant
amplitude
transversal sweep

Vertical sweep +
synchronized
amplitude
transversal sweep


OPEN



THALES

03

First prototype test result summary





OPEN

THALES

First prototype test result summary

Short pulse test at KIT in 2016

- 1 MW P_{out} for 5 ms pulse ($I_{beam} \sim 48$ A)
- 850 kW for 180 s - stable at 170.22 GHz (pulse duration limit of the KIT test stand)
- Measured frequency shift: 400 MHz at 800 kW
- Verified modulated regime up to 5 kHz for neoclassical tearing mode (NTM) stabilization



First prototype test result summary

7th ITG International Vacuum
Electronics Workshop (IVEW) 2020

CW test at EPFL-SPC in 2018

- Operation in ITER relevant conditions (MOU, corrugated waveguide transmission line)
- Results similar to 2016 campaign
 - Maximal pulse length 250 s, limited by external factors (overheating in MOU)



$P \sim 0.8 \text{ MW}$


Item	Target value & range	Outcome (EGYC)
HV design of the gyrotron	96 kV for cathode	Validated
Nominal frequency	$170 \pm 0.3 \text{ GHz}$	Validated
TEM_{00} mode purity at the window	>95%	Validated
Alignment of the output RF beam	<10 mm	Validated
Pulse length and stability of vacuum & temperature	180 s	Validated
Vacuum level, temperatures and stray losses	Operation at 180s compatible with CW conditions	Validated
Nominal output power	1.0 MW	$0.8 \text{ MW} < P < 1 \text{ MW}$
RF power generation efficiency (in depressed-collector operation)	50%	$38 \% < \eta < 50 \%$ (Limited body voltage)

OPEN

THALES

04

First prototype expertize



OPEN

Subject

- While waiting for test stand repairing, the 1st prototype has been opened for status investigations

Collector and mirror box

- Standard operation signatures
- Collector perfectly vacuum tight
- Minor mechanical deformations
- No traces of typical process (nickeling, sand-blasting..)
- Four ion getter pumps perfectly maintained and isolating structure still compatible with 5 kV operation




Gun and beam Tunnel

- No arcing, outgassing or oxidation signatures
- Emitter homogeneity $\Delta T \leq 19^\circ\text{C}$
- Considerable emitter shrank. Cause production yield: in ~0.1% cases after high temp cycles
- Beam tunnel in excellent status

Interaction cavity

- Minor overheating signatures
- Plastic deformations in the order of 10 μ m radial deviation



Mechanical measurements

- Robotized arm measurements of subassemblies respect to desired position
- Base plate ring as reference element
- Misalignments detected on body and gun. Cause: severe constraints exerted by complex hydraulic circuit (served for isolated cavity calorimetry)


Expertize resume

- Body misalignment compensated by adjusting gyrotron position in the SCM
- Defects can critically influence the output capability:
 - Emitter misalignment
 - Cavity deformation

Sub assembly	Diagnosis	Status
Collector	Minor deformation	✓
Vacuum pumps	Clean, tight	✓
Mirror box	Clean, tight, no arcing	✓
Body (Mirror plate)	Misalignment	✗
CVD Window	No oxidization, no arcing	✓
Relief window	Clean, tight	✓
Cooling circuits	Clean, tight	✓
Launcher	No oxidization, no arcing	✓
Cavity	Deformations, Misalignment	✗
Beam tunnel	No oxidization, no arcing	✓
Electron gun	Misalignment, Emitter shrinking	✗

05

Gyrotron evolution





OPEN

THALES

Alignment improvement

- Simplification of the cooling circuit to reduce mechanical constraints exerted by pipes
- Implementation of systematic iterative measurements after each welding



Electric feedthrough improvement


- Increase feedthrough dimension and distances from shield to permit higher HV depression
- Optimized shape: the max E field is 4.5kV/mm @ 35 kV of body voltage

Cavity improvement

- Extended interaction region => $P_{cav} + 15\%$
- Extended Raschig zone towards the up-taper
- Adoption of a qualified (TH1510-like) up-taper structure => improve water speed


Emitter improvement

- Cathode upgrade with improved centering structure
- Adoption of cathode checking procedure before and after activation



06

Summary and perspective



OPEN

THALES

Continuous progress

- First 170 GHz ITER gyrotron TH1509 prototype manufactured, tested and expertized
- The upgraded prototype, TH1509U is being manufactured and it will be tested in 2020
- Two dual frequency (84-126 GHz) gyrotrons operative on TCV tokamak at EPFL-SPC
- Nine 140 GHz gyrotrons daily energizing the W7-X stellarator with outstanding reliability



TH1507 Upgrade

- 1.5 MW
- $TE_{28,10}$
- 56 A e-beam
- hybrid launcher
- Improved collector
- 175GHz @ $TE_{36,12}$



Final considerations

- Example of synergy between academic institutions and the industry to overcome the state of the art
- Important contribution to fusion community
- Large confidence in the robustness of the future ITER and TCV Thales programs and the upstarting W7-X 1.5 MW tube upgrade

Gyrotron Workshop: New assembly clean room

- Clean room dedicated to scientific products
- Modernization and new assembly tools for klystron and gyrotron manufacturing
- Increase the production capability



Gyrotron Workshop: New assembly clean room

- Precise alignment of sub-assemblies during final integration
- High temperature bake-out for high vacuum quality and quick tube conditioning
- Final 3D control before shipment



Actual delivered tubes

- 2003-2011: 10 TH1507 tubes delivered (140 GHz)
- 2013-2017: 1 TH1509 prototype delivered (170 GHz)
- 2016-2019: 2 TH1510 tubes delivered (84/126 GHz)

Model
Frequency (GHz)
Pulse length (s)
Measured P_{out} (MW)
Measured Efficiency
Interaction Mode
Acceleration Voltage
B_{cav} (T)
Beam Current (A)



TH1507
140
1800
1.0
40%
TE _{28 8}
80
5.6
40

The 140 GHz gyrotron for the stellarator W7-X



TH1509 (Proto 1)
170
3600
$0.8 < P < 1.0$
$38 \% < \eta < 50 \%$
TE _{32 9}
80
7.0
40

The European 170 GHz gyrotron prototype for ITER





TH1510 (Tube 1)
84 - 126
2
0.95 - 1.0
35% - 36% (Undepressed)
TE _{17 5} - TE _{26 7}
80
3.0-5.0
40

The true dual frequency gyrotron
~Same power output by two different interaction modes

OPEN

On behalf the TH1509 gyrotron team



Thanks for the Attention

This work is partially supported by F4E under contract F4E-OPE-992 to THALES and Grant F4E-GRT-553 to European Gyrotron Consortium (EGYC). The views expressed in this publication are the sole responsibility of authors and do not necessarily reflect the views of F4E, European Commission or ITER Organization.