

# Status of the Gyrotron Multistage Depressed Collector Development at KIT

C.Wu, I.Pagonakis, S.Illy, D.Albert, K.Avramidis, G.Gantenbein, M.Thumm, J.Jelonnek


Institute for Pulsed Power and Microwave Technology



This project has received funding from the European Union's Horizon 2020 research and innovation program under grant agreement number 633053. The views and opinions expressed herein do not necessarily reflect those of the European Commission.


# Motivation

## Today: ITER



- $f = 170 \text{ GHz}$ ,  $P_{\text{RF}} = 1 \text{ MW}$
- Gyrotron  $\eta_{\text{total}} = 50 \%$

## Future: DEMO



- $f = 170 / 204 \text{ GHz}$ ,  $P_{\text{RF}} = 2 \text{ MW}$
- Requires gyrotron  $\eta_{\text{total}} > 60 \%$

For a 50 MW ECRH system, increase  $\eta$  from 50 % to 63 %

➔ **Saves 20 MW input power** ➔ increases fusion gain factor

# Introduction: Gyrotron Efficiency

Definition of the gyrotron overall efficiency:

$$\eta_{\text{total}} = \frac{\text{Output RF power}}{\text{Input DC power}}$$

# Introduction: Gyrotron Efficiency

**Interaction efficiency**

$$\eta_{\text{int}} \approx 35 \%$$

**RF efficiency**


$$\eta_{\text{RF}} \approx 90 \%$$

**Collector efficiency**

$$\eta_{\text{col}} \approx 60 \% \text{ (single stage)}$$

$$\eta_{\text{total}} = \frac{\text{Output RF power}}{\text{Input DC power}}$$

# Introduction: Gyrotron Efficiency



# Introduction: Gyrotron Efficiency

**Interaction efficiency**

$$\eta_{\text{int}} \approx 35 \%$$

**RF efficiency**

$$\eta_{\text{RF}} \approx 90 \%$$


**Collector efficiency**

$$\eta_{\text{col}} \approx 60 \%$$
 (single stage)

**Overall efficiency**


$$\eta_{\text{total}} = \frac{\eta_{\text{int}} \eta_{\text{RF}}}{1 - (1 - \eta_{\text{int}}) \eta_{\text{col}}}$$

→ A collector efficiency of **74 %** is required



# Introduction: Spent Electron Beam

## ■ The small-orbit hollow spent electron beam in gyrotron



■ 45 A, **2.5 MW** in the 170 GHz 1 MW gyrotron


■ Magnetic field confines the electron beam

■ At the end of the gyrotron cavity

■  $r_{gc} \approx 9.9 \text{ mm}$ ,  $r_L \approx 0.1 \text{ mm}$ ,  $B \approx 6.2 \text{ T}$

➔ **High magnetic flux** (conserved in the most situations)


## ■ Distribution of the electron kinetic energy



$$\eta_{\text{col}} = \frac{\text{Recovered beam power}}{\text{Total beam power}}$$

# Introduction: Depressed Collectors

## Single-stage Depressed Collector (SDC)




Recovered beam power

$$P_{\text{rec,SDC}} = U_d \cdot I_b$$

$$= U_{d1} \cdot I_{b1} + U_{d1} \cdot I_{b2}$$

## Multistage Depressed Collector (MDC)



$$P_{\text{rec,MDC}} = U_{d1} \cdot I_{b1} + U_{d2} \cdot I_{b2}$$


**No MDC for gyrotrons exist**

*An MDC recovers more power than the SDC.*

→ An MDC can further improve the efficiency


# The Reference SDC

- Final target:  
170 GHz / 204 GHz, 2 MW  
coaxial gyrotron for DEMO
- However, taking the SDC of  
the 170 GHz 1 MW gyrotron  
as reference
  - 30 kV depression voltage
  - $L = 1.33$  m
  - $R = 255$  mm
  - Time-averaged power load  
(beam sweeping)  $< 500$  W/cm<sup>2</sup>
- Extrapolation for the DEMO  
gyrotron will be discussed



# Challenges for the Gyrotron MDC Concept

- Moderate magnetic field in gyrotron collector
  - $B = 100 \text{ mT}$  at the collector entrance,  
 $B = 10 \text{ mT}$  at 1 m axial distance away from the entrance
  - ➔ concepts for TWT MDCs (require  $B \ll 1 \text{ mT}$ ) do not work
- Small orbits electron beam enclosing a high magnetic flux



**Example:** reducing the  $B$  field to 1 mT requires a radius of



$$R = \frac{\pi (9.9 \text{ mm})^2 6.2 \text{ T}}{\pi 0.1 \text{ mT}} = 0.78 \text{ m}$$

➔ Results in a large collector size

- Busch's theorem indicates that the sorting of orbits is not possible in an axisymmetric system with moderate magnetic field
- In addition, there is a high beam power

# Proposals Prior to This Work

There were two kinds of design proposals prior to this work




- Axisymmetric (2D)
- $B < 1 \text{ mT}$
- Electric field dominates the sorting
- Hard to scale to a higher frequency

- Non-axisymmetric (3D)
- $B = 26 \text{ mT}$
- Use  $E \times B$  drift to sort electrons
- Lack of 3D simulation possibility at that time, therefore infinite stages

# MDC Type 1: the Axisymmetric Concept


Example: an ideal non-adiabatic transition of magnetic field



- Transition from a uniform  $B = 100$  mT to  $B = 10$  mT
- Electron with energy from 30 keV to 90 keV

# MDC Type 1: the Axisymmetric Concept


Example: an ideal non-adiabatic transition of magnetic field



■ Electrodes collect the beam electrons at the proper positions

# MDC Type 1: the Axisymmetric Concept


Example: an ideal non-adiabatic transition of magnetic field



- Electrodes collect the beam electrons at the proper positions

# MDC Type 1: the Axisymmetric Concept

- Conceptual design according to this principle, similar size as the SDC



- $\eta_{\text{col}} = 73 \%$  w/o secondary electrons, reduced to 65 % with s.e.
- Power density  $< 500 \text{ W/cm}^2$  w/o secondary electrons
- $\eta_{\text{col}}$  may be reduced by 10 %, if there is an external  $B$  or misalignment

The efficiency cannot be further improved, since


**There is no separation of orbits**

## MDC Type 2: the Concept Using $E \times B$ drift

### The electric field causes a charged particle to drift

- The drift velocity  $\mathbf{v}_d = \mathbf{E} \times \mathbf{B} / B^2$
- Independent of mass, velocity and charge
- Can be used to sort and even **separate** the electron orbits


### Principle of an $E \times B$ MDC



## MDC Type 2: the Concept Using $E \times B$ drift



The electric field causes a charged particle to drift

- The drift velocity  $\mathbf{v}_d = \mathbf{E} \times \mathbf{B} / B^2$
- Independent of mass, velocity and charge
- Can be used to sort and even **separate** the electron orbits




Numerous design proposals  
have been investigated at KIT

# Design Proposal Using Helical Electrodes





- Azimuthal  $E$ -field component  $\rightarrow$  Radial drift
- Two-stage, but extendable if necessary
- Requires 3 tuning coils ( $\Delta B < 20$  mT)


# Principle



# Principle




# Properties of This Proposal




- The simplest collector coil system among all designs
- $\eta_{\text{col}} = 76 \%$  (incl. secondary electrons)
  - Well handling of secondary electron ( $\Delta\eta_{\text{col}} = 1 \%$ )
  - $\eta_{\text{col}}$  is insensitive to external  $B$  field and misalignment
- Power Load density for the 1 MW gyrotron
  - 1<sup>st</sup> stage: 300 W/cm<sup>2</sup>
  - 2<sup>nd</sup> stage: 700 W/cm<sup>2</sup> → sweep

} Will be doubled for DEMO sweeping mandatory
- Compared to the SDC: length -10 %, width +30 %
- 700 mA back-stream current (incl. secondary elect.)

# Upgrade 1: Suppress the Back-Stream Current



Proposal 1: disk to collect the reflection




Proposal 2, based on p.1


➔ Back-stream current can be reduce  
from 700 mA to 22.5 mA (incl. secondary electrons)

## Upgrade 2: Multiple Helical Electrodes

- $N$  helices to separate stages, instead of one
- Helix length is reduced to  $1/N$ , while the drift velocity  $\mathbf{v}_d = \mathbf{E} \times \mathbf{B} / B^2 = E B \sin(\alpha)$  keeps constant
- Simulation shows for  $N = 3$ 
  - Same  $\eta$  as with only one helix
  - 45 mA with secondary electrons
  - $P_{\text{disk}} = 400 \text{ W}$  (the 1 MW gyrotron)




# Engineering Design of a Short-Pulse Prototype




- +30 kV at gyrotron body (cavity)
- Ground potential at the
  - vacuum envelope
  - 1<sup>st</sup> stage
  - gyrotron mirror box
- -12 kV at the second stage
- Approximately 300 kg
  - 30 % shorter than the ref. SDC
  - totally 60 % wider than the SDC

# Engineering Design of a Short-Pulse Prototype



- +30 kV at gyrotron body (cavity)
- Ground potential at the
  - vacuum envelope
  - 1<sup>st</sup> stage
  - gyrotron mirror box
- -12 kV at the second stage
- Approximately 300 kg
  - 30 % shorter than the ref. SDC
  - totally 60 % wider than the SDC

# Engineering Design of a Short-Pulse Prototype



- +30 kV at gyrotron body (cavity)
- Ground potential at the
  - vacuum envelope
  - 1<sup>st</sup> stage
  - gyrotron mirror box
- -12 kV at the second stage
- Approximately 300 kg
  - 30 % shorter than the ref. SDC
  - totally 60 % wider than the SDC


# Conclusion

- $\eta_{\text{col}} > 74 \%$  is required for DEMO
- Two fundamentally different concepts
  - Axisymmetric geometry and fields  $\leftarrow$  no separation of cyclotron orbits
  - Using the  $\mathbf{E} \times \mathbf{B}$  drift (breaks the axisymmetry)  $\leftarrow$  more promising
- Numerous design proposed for the  $\mathbf{E} \times \mathbf{B}$  drift concept  
The proposal using helical electrodes (azimuthal  $\mathbf{E}$ ) is promising
  - $\eta_{\text{col}}$  is expected to be 76 %
  - Upgrades of the basic design should be considered
  - Engineering design is presented
- Extrapolation to the DEMO 2 MW gyrotron
  - Doubled back-stream beam current (might be  $> 90 \text{ mA}$ )
  - Doubled load, especially at the 2<sup>nd</sup> stage: sweeping required

# BACKUP SLIDES


# Power Load Density 1<sup>st</sup> Stage

- Top view of the first stage
- 170GHz, 1MW gyrotron as reference
  - $I_{\text{beam}} = 45 \text{ A}$
  - $P_{\text{beam}} = 2.5 \text{ kW}$
- Peak load < 300 W/cm<sup>2</sup>




## Power Load Density 2<sup>nd</sup> Stage


- Peak load  $700 \text{ W/cm}^2 > 500 \text{ W/cm}^2 \rightarrow$  electron beam might be swept
- Extrapolation for a 2 MW gyrotron:  $1.4 \text{ kW/cm}^2 \rightarrow$  sweeping necessary



# Possibilities to Produce $E \times B$ Drifts




# Proposals Investigated at KIT




# Influence of electron beam displacement

- Electron beam can be misaligned up to 0.8 mm **in cavity**





sufficient tolerance to  
beam misalignment




# Influence of external magnetic field

- Transversal stray field of the Tokamak up to 5 Gs



## Other advantages

- Shrink the length of magnetic recondition  $\rightarrow$  reduce # of coils



- Further simplify the magnet system

