

SIMULATIONS TOWARDS THE GENERATION OF ULTRA-SHORT PULSES WITH COUPLED GYRO-DEVICES

A. Marek, K. A. Avramidis, S. M. Copplestone, N. S. Ginzburg, S. Illy, J. Jelonnek, J. Jin,
P. Ortwein and M. Thumm

INSTITUTE FOR PULSED POWER AND MICROWAVE TECHNOLOGY,
FACULTY OF ELECTRICAL ENGINEERING AND INFORMATION
TECHNOLOGY




Structure

- **Generation of ultra-short microwave pulses**
- **Components of the feedback loop and ‘cold’ simulations**
 - Gyro-TWT with helical interaction region
 - Quasi-optical mirror system
- **PIC simulations with PICLas**
 - Overview PICLas
 - Non linear absorber at 30 GHz
- **Conclusion**


Generation of Ultra-Short Microwave Pulses

- **Joined RSF-DFG Project (IAP-RAS and KIT-IHM)**
- Method of **passive mode locking** (as in laser physics)
→ Feedback loop of amplifier and saturable absorber
- Amplifier: high amplification of ultra short pulses
- Non linear absorber: absorption of low power signals, transmission of high power signals



Generation of Ultra-Short Microwave Pulses

- **Joined RSF-DFG Project (IAP-RAS and KIT-IHM)**
- Method of **passive mode locking** (as in laser physics)
→ Feedback loop of amplifier and saturable absorber
- Amplifier: high amplification of ultra short pulses
- Non linear absorber: absorption of low power signals, transmission of high power signals



Generation of Ultra-Short Microwave Pulses


- Pulse **duration** is determined by the **bandwidth** of the absorber
- Pulse **distance** is determined by the **time** for passing through the feedback loop
- Pulse **power** is limited by the output-power of the **amplifier**

- Target frequency: **260 GHz**
- First prove of concept: **30 GHz**

For 30 GHz

Duration:	0.25 ns (→ absorber bandwidth \approx 5 GHz)
Distance:	5 ns
Power:	300 kW


Generation of Ultra-Short Microwave Pulses



- Amplifier and absorber could be realized as **gyro-TWTs with helical waveguide**
 - Gyro-TWT as amplifier: optimized for amplification of ultra-short pulses
 - Gyro-TWT as saturable absorber: operating in the Kompfner dip regime
 - Both Gyro-TWTs with single window input/output
- Amplifier and absorber coupled with a **quasi-optical mirror system**
 - Polarization splitter as tunable semitransparent reflector

Components of the feedback loop

Gyro-TWT with helically corrugations



- Gyro-TWT with helical corrugated interaction region


$$r = r_0 + h_0 \cos(m_B \varphi - 2\pi z/d)$$

- Corrugation couples modes which fulfill:

$$m_1 - m_2 = m_B \quad \text{and} \quad h_1 - h_2 = 2\pi/d$$



- Single window input/output

- $m_B = 3 \rightarrow$ coupling of $TE_{2,1}$ and counter-rotating $TE_{-1,1}$ mode to $TE_{2,1}$ like eigenmode





Single window input/output

Amplifier section for 260 GHz:



Dispersion of Helically Corrugated Waveguides


- Optimized dispersion relation by coupling of $TE_{2,1}$ and $TE_{-1,1}$ mode
- Perturbation theory not usable for high corrugation amplitudes
- Simulation of the dispersion with own MoM-EFIE-Code:
- Frequency-Domain \rightarrow Simulations at different frequencies
- Spatial Fourier transformation of the radial electric field E_r along a line parallel to the z-axis




Quasi-Optical Mirror System for the Feedback Loop

Required:

- Semi transparent mirror:
 - Non-transparent in Amplifier-Absorber direction
 - Semi-transparent in Absorber-Amplifier direction
 - Suitable for high energies
 - Available for 30 GHz up to the sub-THz range
 - Tunable reflection coefficient





Quasi-Optical Mirror System for the Feedback Loop




s of the devices are
signals is possible

ing as polarization s
out/output channels

ent mirror realized
ient can be adjuste




Quasi-Optical Mirror System for the Feedback Loop



Simulated results (250 | 260 | 270 GHz):

- Up-reflection arm:
 - Power efficiency: (97 % | 99 % | 97 %)
 - Extinction ratio: (17 dB | 23 dB | 16 dB)
 - Back-Reflection: (-39 dB | -38 dB | -34 dB)
- In-plane-reflection arm:
 - Power efficiency: (98 % | 99 % | 99 %)
 - Extinction ratio: (17 dB | 22 dB | 21 dB)
 - Back-Reflection: (-42 dB | -40 dB | -37 dB)



From Literature (200 GHz):

- Transmission arm:
 - Power efficiency: 96 %
 - Extinction ratio: 42 dB
- Reflection arm:
 - Power efficiency: 96 %
 - Extinction ratio: 28 dB

PIC simulations of the non-linear absorber with PICLas

PICLas

- Developed at Institut für Aerodynamik und Gasdynamik (**IAG**) and Institute of Space Systems (**IRS**), Universität Stuttgart
- Full-wave simulations via **Particle-In-Cell**
 - Maxwell's equations on hexahedral meshes via **high-order** Discontinuous Galerkin Spectral Element Method
 - Vlasov's equation via 6d macro particle approximation with Lorentz forces
- **Curvilinear mesh** of arbitrary order
- Support for **Super-Computers** → can run on >100000 Cores
- Full access to the source-code → **no 'black box'**




High Order Mesh Generation

- Mesh creation with **HOPR**
- Open source tool developed from Aerodynamik und Gasdynamik (IAG), Universität Stuttgart
- New algorithm for the creation of an optimal mesh for helical structures


→ **Optimized Curvilinear mesh of arbitrary order**

$$r = r_0 + h_0 \cos(m_B \varphi - 2\pi z/d)$$



Simulation Setup

- Absorbing boundaries (PML) at beginning and end of the geometry
→ avoid reflections
- Particle insert inside the PML
→ avoid radiation from the inserting process
- Insertion of the input signal at the end of the PML
- Separation of e⁻ beam and RF by a B_z decrease



Simulations for a feedback loop at 30 GHz

- Feedback loop at 30 GHz
- Simulations in “N. S. Ginzburg, et al. *IEEE Transactions on Electron Devices* 65.6 (2018): 2334-2339” are performed with CST
→ Reproduction of the same simulations with PICLas

- Absorber


■ Current:	$I = 2.4 \text{ A}$	Waveguide radius:	$r_0 = 0.4 \text{ cm}$
■ Beam voltage:	$U = 54 \text{ kV}$	Corrugation amp.:	$h = 0.1 \text{ cm}$
■ Pitch factor:	$\alpha = 0.53$	Corrugation per.:	$d = 1.0 \text{ cm}$

- Amplifier

■ Current:	$I = 10 \text{ A}$	Waveguide radius:	$r_0 = 0.4 \text{ cm}$
■ Beam voltage:	$U = 68 \text{ kV}$	Corrugation amp.:	$h = 0.06 \text{ cm}$
■ Pitch factor:	$\alpha = 1.2$	Corrugation per.:	$d = 1.2 \text{ cm}$


Simulations of a Gyro-TWT Operating as Saturable Absorber

- Operates in the so-called Kompfner-Dip regime
→electromagnetic wave is absorbed by the e^- beam
- Realized by a small detuning of the resonant guiding magnetic field ($0.59 \text{ T} \rightarrow 0.6 \text{ T}$)
- Group velocity should be close to the axial velocity of the e^- beam
→electromagnetic pulse interacts with a specific fraction of the e^- beam



Simulations of a Gyro-TWT Operating as Saturable Absorber


- Saturable Absorber: Signal with low amplitude → high attenuation
Signal with high amplitude → low attenuation
- Transmission coefficient: $K = P_{\text{out}} / P_{\text{in}}$
- Gaussian pulse with $f = 30$ GHz and $\sigma = 0.5$ ns



Mechanism of Saturable Absorber

- Group velocity \approx axial velocity
- RF transfers energy to a specific fraction of the e⁻ beam
- High energy transfer > 30 kW
→ e⁻ beam comes into the amplification regime



RF-Power along the interaction-region





Absorption of Short Pulses

- The length of the generated pulses in the feedback loop depends on the bandwidth of the gyro-devices
- Target pulse-length: 0.25 ns \rightarrow required bandwidth > 5 GHz

Pulse-length: 1 ns




Pulse-length: 0.25 ns




Cyclotron Absorber with Rectilinear e⁻ Beam

- Absorber with rectilinear e⁻ beam
- Cyclotron absorption
- Operates at the fundamental cyclotron harmonic → $B \approx 1 \text{ T}$
- Beam parameter: $I \approx 1.2 \text{ A}$
 $E \approx 55 \text{ keV}$




Cyclotron Absorber with Rectangular e⁻ Beam

- Group velocity \approx axial velocity
- RF transfers energy to a specific fraction of the e⁻ beam
- Bandwidth > 5 GHz
- High energy transfer > 30 kW
 - e⁻ beam comes into the amplification regime




Cyclotron Absorber with Rectangular e^- Beam

- Absorption of a 0.25 ns Gaussian pulse with 10 kW power



Cyclotron Absorber with Rectangular e^- Beam

- Absorption of a 0.25 ns Gaussian pulse with 10 kW power



Conclusion & Outlook

Conclusion

- Design of a simple quasi-optical feedback-system
- Qualified setup for accuracy full-wave PIC simulations with PICLas
- Two concepts of sturable absorbers

Outlook

- Full simulation of the complete system of amplifier and absorber
- Simulation with more realistic beam parameters (α -spread, ...)
- First experiments end of the year (at the IAP)

