

Oscillation Starting Current Approximation by Time-Domain Simulation in Traveling-Wave Tubes

Moritz Hägermann¹, Philip Birtel², Arne F. Jacob¹

¹Hamburg University of Technology,
Institute of High-Frequency Technology, Germany

²Thales Electronic Systems GmbH, Ulm, Germany

ITG Workshop, Bad Honnef
Traveling-Wave Tubes - September 7th, 2018




- ① Introduction
- ② Oscillation Simulation
- ③ Starting Current Approximation
- ④ Conclusion

Traveling-Wave Tubes

RF power amplifier

- High output power and gain
- Large bandwidth
- Efficiency
- Robustness




Thales, TH 4816RC



DLR Small-Geo, ESA, P. Carril

Traveling-Wave Tubes



Simulation Tools: General vs. Special Approach

General approach: 3D PIC Solver

- Direct solution of Maxwell's equations + equation of motion
- Full time domain approach

Advantages

- General purpose tool
- Exploration of new concepts

Disadvantages

- High demand on computer resources
- Long run-time ($\sim 1/2$ day)

e.g. CST Particle Studio

→ Not an efficient tool for design process

Simulation Tools: General vs. Special Approach

General approach: 3D PIC Solver

- Direct solution of Maxwell's equations + equation of motion
- Full time domain approach

Advantages

- General purpose tool
- Exploration of new concepts

Disadvantages

- High demand on computer resources
- Long run-time ($\sim 1/2$ day)

e.g. CST Particle Studio

→ Not an efficient tool for design process

Special approach: 2.5D Hybrid Solver

- Uses known analytical expansion
- Employs axial-symmetry inside the beam tunnel

Advantages

- Computationally efficient (run time ~ 1 min)

Disadvantages

- Device specific
- Certain effects are not modeled

MVTRAD = "MouVement RADial"

→ Useful for designing and optimizing


Instabilities in Traveling-Wave Tubes

- Coupled system of RF-fields and electron beam can lead to instabilities
 - Backward-wave oscillations
 - Band-edge oscillations
 - π -Mode oscillations
 - Drive-induced oscillations
- Excitation from noise or RF drive-level
- Occurrence depends on beam current and/or RF power
- Lower boundary for beam current: oscillation starting current


Here: π -Mode oscillation analysis with CST Particle Studio

- ① Introduction
- ② Oscillation Simulation
- ③ Starting Current Approximation
- ④ Conclusion

Homogeneous Tube Section




Dispersion




E-Field and Coupling at Band Gap


Lower band edge:
70.3 GHz



coupling ≈ 0



Upper band edge:
72.1 GHz





coupling $\rightarrow \infty$

Simulation Parameters

- Serpentine folded-waveguide delay-line
- Homogeneous tube section ~ 60 mm
- Material: lossy metal $\sigma = 3.9 \cdot 10^7$ S/m
- Electron beam: ~ 28 kV beam voltage
 - Beam voltage chosen to force an oscillation
- PPM focusing field
- Waveguide ports without excitation
- Oscillation excites from noise of the beam start up

CST Time Signals



Stable and saturated oscillation at 71.7 GHz with ~ 650 W (340 mA beam current)

- ① Introduction
- ② Oscillation Simulation
- ③ Starting Current Approximation
- ④ Conclusion

Oscillation Start Up

Problem in time-domain simulation tools:
 $t_{\text{sim}} \rightarrow \infty$ at/below oscillation starting current

Oscillation startup:

$$a(t) = B \cdot e^{\alpha t} \cdot \cos(\omega_{\text{osc}} t)$$

- Assumption: $\alpha = \alpha(I)$ and $B = B(I)$
- At oscillation starting current I_{SC} : $\alpha(I_{\text{SC}}) = 0$ or $B(I_{\text{SC}}) = 0$
- Simulation at $I_1, I_2 > I_{\text{SC}}$, where
 - $\alpha(I_1), \alpha(I_2) > 0$
 - $B(I_1), B(I_2) > 0$

→ Interpolate α or B to calculate I_{SC}

Oscillation Start Up

Problem in time-domain simulation tools:
 $t_{\text{sim}} \rightarrow \infty$ at/below oscillation starting current

Oscillation startup:

$$a(t) = B \cdot e^{\alpha t} \cdot \cos(\omega_{\text{osc}} t)$$

- Assumption: $\alpha = \alpha(I)$ and $B = B(I)$
- At oscillation starting current I_{SC} : $\alpha(I_{\text{SC}}) = 0$ or $B(I_{\text{SC}}) = 0$
- Simulation at $I_1, I_2 > I_{\text{SC}}$, where
 - $\alpha(I_1), \alpha(I_2) > 0$
 - $B(I_1), B(I_2) > 0$

→ Interpolate α or B to calculate I_{SC}

Problem in time-domain simulation tools:
 $t_{\text{sim}} \rightarrow \infty$ at/below oscillation starting current



Oscillation startup:

$$a(t) = B \cdot e^{\alpha t} \cdot \cos(\omega_{\text{osc}} t)$$

- Assumption: $\alpha = \alpha(I)$ and $B = B(I)$
- At oscillation starting current I_{SC} : $\alpha(I_{\text{SC}}) = 0$ or $B(I_{\text{SC}}) = 0$
- Simulation at $I_1, I_2 > I_{\text{SC}}$, where
 - $\alpha(I_1), \alpha(I_2) > 0$
 - $B(I_1), B(I_2) > 0$


→ Interpolate α or B to calculate I_{SC}

Port Signals




logarithmic scale

Port Signal Analysis




$$\log(a(t)) = \log(B) + \alpha t$$



$$\rightarrow \alpha = \alpha(I)$$

$$\rightarrow B \neq \text{fct}(I), \text{ only time shift}$$



Slope vs. Beam Current




$$\alpha = m \cdot \log(I) + b, I > I_{sc}$$

- $\alpha \neq 0$ in simulation
- Problem: amplified noise


⇒ Additional information from spectral analysis and oscillation power



Estimated Oscillation Starting Current



⇒ Estimated starting current
 $I_{SC} = 103.5$ mA



- Spectral components at f_{Osc} vanish between 100 mA and 120 mA
- ⇒ Starting current from simulation [100 mA, 120 mA]

⇒ Error [0.0 %, 13.8 %]

- ① Introduction
- ② Oscillation Simulation
- ③ Starting Current Approximation
- ④ Conclusion

- Various oscillations can occur in traveling-wave tubes
- Time-domain simulation offers geometry driven approach
- Simulation at or below starting current takes time
- Analysis of oscillation startup provides an approximation of the starting current

- Explicit definition of starting current in CST necessary
 - e.g. extended model including oscillation power or spectral information
- Influence of beam current rise during switch-on on oscillation startup
- Verification by other geometries (e.g. helix TWTs)
- Simulation and verification by other instabilities (e.g. BWO)

Thank you for your attention!

Acknowledgments

Funded by the German Space Agency (DLR) on behalf of the Federal Ministry of Economics and Technology (BMWi).

